

Declaration of Performance

Nr.002-CPR-20-03-2018



1) Unique identification code of the product-type:

Loke 40, Frigg 25, Frigg 30, Frigg 40, Hugin 50, Loke Strong WFC 40

2) Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

See product label.

3) Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Acoustic Wall Panel.

4) Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

PROSO AS and Norsk Akustikkcenter AS, Djupadalskroken 26, 4046 Hasrsfjod, Norway.

5) Name and address to approved representative according Article 12(2):

Not relevant.

6) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1.

7) In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 13964 : 2014 and EN 15102:2007/A1:2011

Exova(UK) Limited trading as Warrington Certification

Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK

Notified body No. 1121

8) If DoP concerns a construction good for which an european technical assessment has been made:

Not relevant.

9) Declared performance:

	Loke 40	Frigg 25	Frigg 30	Frigg 40	Hugin 50	Loke Strong WFC 40
Reaction to fire						
- boards core	A2-s1, d0					
- surface tissue	A2-s1, d0					A2-s1, d0
- black fabric surface		C-s2, d0	C-s2, d0	C-s2, d0	C-s2, d0	
- grey fabric surface		C-s2, d0	C-s2, d0	C-s2, d0	C-s2, d0	
- white fabric surface		C-s2, d0	C-s2, d0	C-s2, d0	C-s2, d0	
Formaldehyde class	E1	E1	E1	E1	E1	E1
Sound absorption α_w	1.00	0.90	0.65	1.00	1.00	0.9
Sound insulation R_w	12dB					
Flexural strength	NPD	NPD	NPD	NPD	NPD	NPD
light reflectance	84%	NPD	NPD	NPD	NPD	white 81%
Shatter Properties	NPD	NPD	NPD	NPD	NPD	NPD
Thermal conductivity	NPD	NPD	NPD	NPD	NPD	NPD
MSDS(Material Safety Data Sheet)	Don't contain any harmful substance mentioned in CAS A20	Don't contain any harmful substance mentioned in CAS A20	Don't contain any harmful substance mentioned in CAS A20	Don't contain any harmful substance mentioned in CAS A20	Don't contain any harmful substance mentioned in CAS A20	Don't contain any harmful substance mentioned in CAS A20
Emission of particulate matter	Not detected according to test GB/T 18883-2002					

NPD = No performance determined

* measured with 50mm air for Loke 40, Frigg 25 and Frigg 40; 0mm for Frigg 30 and Loke Strong WFC 40; 1000mm for Hugin 50

10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

General manager Tang Jian Feng

