

Declaration of Performance

Nr.002-CPR-08-03-2017



1) Unique identification code of the product-type:

Loke 40, Frigg 25, Frigg 30, Hugin 50

2) Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

See product label.

3) Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Acoustic Wall Panel

4) Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Proso AS, Djupadalskroken 26, 4046 Harsfjord, Norway.

5) name and address to approved representative according article 12, nr 2.

Not relevant.

6) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1.

7) In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Loke 40 B :

EN13964:2014

Warrington Certification Limited, Holmesfield Road, Warrington, Cheshire, WA12DS, UK.

Notified body No. 1121

Frigg 25, Frigg 30, Hugin 50:

Fire performance testing done according to CE EN 13501-1:2007

Formaldehyde emission testing done according to CE EN 717-1:2004.

Sound absorption testing done according to ISO 354:2003; CE EN 11654:1997

8) If DoP concerns a construction good for which an european technical assessment has been made:

Not relevant.

9) Declared performance:

	Loke 40 B	Frigg 25	Frigg 30	Hugin 50
Reaction to fire:				
- boards core	A2-s1, d0	A2-s1, d0	A2-s1, d0	A2-s1, d0
- surface tissue	A2-s1, d0			
- black fabric surface		C-s2, d0	C-s2, d0	C-s2, d0
- grey fabric surface		C-s2, d0	C-s2, d0	C-s2, d0
- white fabric surface		C-s2, d0	C-s2, d0	C-s2, d0
Formaldehyde class	E1	E1	E1	E1
Sound absorption α_w	1.00	0,90	0.65	1.00
Flexural strength	NPD	NPD	NPD	NPD
light reflectance	84%	NPD	NPD	NPD
Shatter Properties	NPD	NPD	NPD	NPD
Thermal conductivity	NPD	NPD	NPD	NPD

NPD = No performance determined

* measured with 50mm air for Loke 40 and Frigg 25; 0mm for Frigg 30; 1000mm for Hugin 50

10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

General manager Tang Jian Feng



AKUSTIKKSENTER
LYDDEMPING